Siderise B Series Fixing Bracket Solid

Supporting brackets for use in the installation of Siderise Cavity Barriers and Firestops. Available in Galvanised or Stainless Steel depending on project requirements. Supplied in a 25mm width in a range of lengths to suit the required void size.



Application

Siderise B Series brackets are designed for quick and easy installation of specified Siderise products to supported system interfaces. B series brackets are currently supplied for installation with Siderise products such as CW-FS,CW-CB,CVB, RV, CH, EW, TW and RF. Please refer to each individual product technical datasheet and installation instructions to ascertain the correct bracket specification for the application and void dimensions on your project.

Technical Specification

Table1: Bracket Dimensions

| Product Ref. | Length(mm) | Width (mm) | Thickness Galv(mm) | Thickness SS(mm) |
|--------------|------------|------------|--------------------|------------------|
| B65/110 | 220 | 25 | 1.0 | 0.9 |
| B195 | 320 | 25 | 1.0 | 0.9 |
| B355 | 505 | 25 | 1.0 | 0.9 |

Please note: Length of bracket provided is measured in flat form from tip to tip.



Table 2: Pre -Galvanised Mild Steel Properties

| Properties | Value |
|---|---|
| Description | Pre-Galvanised Mild Steel Brackets |
| Grade | DX51-D |
| Tensile Strength Rm(N/mm ²) | 270 - 500 |
| Coating Weight | Z275 Zinc (Min Av triple spot coating mass g/m ²) |
| General Characteristics | Hot Dip Galvanised giving sacrificial protection to all areas after forming and fabrication |
| Dimensional Tolerances | Length +/- 1.0mm, Width and Thickness +/-0.08mm |

Table 3: Stainless Steel Grade 304 Bracket Properties

| Properties | Value |
|---|---|
| Description | Stainless Steel Brackets |
| Grade | 304 |
| Tensile Strength Rm(N/mm ²) | 550-700 |
| General Characteristics | Widely used stainless chromium-nickel steels. General purpose grades with good resistance to atmospheric corrosion and many organic and inorganic chemicals |
| Dimensional Tolerances | Length +/- 1.0mm, Width and Thickness +/-0.08mm |

Note: Stainless steel 316 grade available subject to minimum order quantity. Please contact our customer service team: customer.service@siderise.com for

Technical Support

For technical advice or support please contact: technical.services@siderise.com

For Installation Training or Site Inspections please contact: site.services@siderise.com

For technical advice or support in the Middle East, India or Asia Pacific contact: smetech@siderise.com

Context

The information in this datasheet is believed to be accurate at the date of publication. Siderise has a policy of continuous product improvement and reserves the right to alter or amend the specifications of products without prior notice. Siderise does not accept responsibility for the consequences of using the products described outside of the recommendations within this datasheet. Expert advice should be sought where there is any doubt about the correct specification or installation of Siderise products.

Siderise B Series Fixing Bracket_1_08_20241015_1517

