


Siderise WRX window reveal liners

Siderise WRX sound absorbing window reveal liner system is a decorative and robust reveal liner for use in secondary glazing.



Application

Siderise WRX Window Reveal Liners provide a practical means of improving the sound insulation performance of secondary glazed windows.

Their application to the reveals substantially reduces the reverberant sound field in the void formed between the primary and secondary glazing.

Traditionally, reveal liners have been formed by cutting strips of semi-decorative board products such as ceiling tiles. Unfortunately, numerous practical problems are associated with these materials for this application.

They include: poor resistance to moisture, colour fading, impracticality of cleaning, moisture staining, limited lengths, unattractive cut edges and generally poor sound absorption characteristics.

Benefits

- Excellent sound absorption properties.
- Unaffected by moisture or UV.
- Supplied to exact dimensions.
- Extensive colour range.
- Maintenance free.
- Simple to fix.

Product description

Siderise WRX Window Reveal Liners comprise an absorptive core of dense rock- fibre insulation held within a covering of perforated sheet metal, which is formed around the sides and top of the core.

The dense rockfibre core is of a special construction to provide improved impact resistance. As standard the core is faced on both surfaces with a non-woven glass fabric to provide anti-dusting characteristics whilst remaining acoustically transparent.

The perforated metal covering is normally finished by either polyester powder coating or for aluminium versions by anodising as required.

Where the end of the installed liner would not normally be hidden, such as at corner junctions or for long reveals at butt joints, the metal covering is additionally formed over the end of the liner to provide a neat final appearance.

Installation

Siderise WRX Window Reveal Liners are normally attached directly to the reveals by through fixing using screws with colour matched heads or caps. Alternatively, they can be retained at their edges by metal angle sections of a matching finish.

Angle sections are also useful in concealing any variable gap formed between the liner and the frame due to variations in the reveal width.

The Reveal Liners can also be supplied in an 'edge notched' version. This permits their use in circular windows or any other application involving curved surfaces.

Acoustic Performance

The sound reduction performance of a secondary glazed window is increased by the application of a sound absorptive material to the reveals.

The level of improvement is influenced by a number of factors. Two of particular significance are:

- The ratio of the treatment area to the total internal surface area of the window void.
- The sound absorption coefficient of the applied liner.

The sound absorption characteristics of the Siderise WRX Reveal Liners alters with the liner thickness and method of mounting e.g. direct to a solid background or suspended above a cavity.

Our technical department can provide indicative absorption data for the specific arrangement under consideration.

Typically, the improvement in the SRI (Mean Sound Reduction Index) of the window is in the range 2-5 dB.

Study

An independent study by the British Snoring & Sleep Apnoea Association / NHS was carried out with a before and after use of the Siderise WRX Reveal Liners and a 5dB improvement in overall performance was measured.



Dimensions

Siderise WRX Window Reveal Liners are manufactured to order and therefore can be produced to any practical dimensions. The following sizes are for guidance only and do not represent specific manufacturing limits:

Thickness: 15 - 75mm

Width: 30 - 500mm

Thermal Performance

Thermal conductivity (l) = 0.040 W/m.K (Rockfibre core only).

Maintenance


Siderise WRX Reveal Liners require no maintenance other than periodic cleaning by light vacuuming or wiping with a damp cloth.



Finishes

Siderise 'WRX' Window Reveal Liners are supplied finished in a white Polyester Powder Coating (PPC) as standard. They can however be finished to any stock PPC RAL colour.

Siderise WRX Reveal Liners can also be produced using stainless steel or aluminium instead of the standard coated galvanised mild steel. Aluminium versions can be supplied anodised to any of the normally available commercial colours.



Additional options

The following options are available:

- A range of protective/decorative facings.
- Can be supplied with an 'edge notch' to permit their use in circular windows or any other application involving curved surfaces.

Products available

The following Siderise products for use in suspended ceiling voids are available and can also be specified using NBS Plus:

- Siderise MC mullion overclad system.
- Siderise CVB acoustic void barriers.
- Siderise CBX flexible acoustic barriers.
- Siderise FLX foam based flexible acoustic barriers.
- Siderise AVC acoustic void closures for tops of walls.
- Siderise TW fire stops for profiled decks.
- Siderise foil tape: FT 120/45.

Contact us for a copy of our Siderise ceiling void barrier range brochure.

Further information

Technical support

For further information please contact our technical team at the address below.

Additional information

The following information is available upon request or via download from our website:

- 1/3rd Octave absorption coefficients available on request.
- Safety Data Sheet.

Available CPD's

Contact Siderise for further information on our CPDs:

- Siderise Acoustic Products for Commercial Interiors - Architect Edition.
- Siderise Acoustic Products and Performance with 1/3rd Octave Data - Acoustic Consultants Edition.

Sales & Technical

Sales support

Internal Sales Team
+44(0)1473 827695
sales.sspl@siderise.com

Technical support

Technical Team
+44(0)1473 827695
technical.sspl@siderise.com

Siderise (Special Products) Limited

Lady Lane Industrial Estate, Hadleigh, Suffolk IP7 6BQ
United Kingdom

The information published herein is given in good faith and is believed to be accurate at the time of publication. Please check that this version is current. Siderise has a policy of continuous product improvement and reserves the right to alter or amend the specifications of products without prior notice. Siderise does not accept responsibility or the consequences of using the products and systems described outside of any given recommendations within this document or its other official documentation. Recommendations for use should be verified in regard to the suitability and compliance with actual requirements, specifications and any applicable laws, codes, and regulations. Expert advice should be sought where there is any doubt about the correct specification or installation of Siderise products and systems.